



Secured Dual Band (L1/L5) GNSS Timing Module with Nanosecond Accuracy

## RES720™ Multi-GNSS Timing Module on Carrier Board

### Resilient Timing

The RES720 offers an industry-leading, value-engineered solution for carrier-grade timing products. It is designed to meet the resilient timing requirements mandated by the 2020 Executive Order for positioning, navigation, and timing (PNT) services.

The RES720 module offers unparalleled accuracy to meet the stringent synchronization needs of the next-generation networks in various industry verticals including 5G X-Haul, Smart Grid, Data Center, SATCOM, Calibration Services, and Industrial Automation applications.

### Dual Band

With dual-band multi-constellation capability, RES720 reduces the timing error under clear skies to < 5 nanoseconds without the need for an external GNSS correction service.

Additionally, the RES720 offers the benefit of higher power L5 signals (twice as much power as L1) with its greater bandwidth, and advanced signal design lowers the risk of interference and improves multi-path protection. The multi-band capability of the RES720 allows it to compensate for the ionosphere error while reducing the timing error under clear skies to a few nanoseconds without further need for correction.

The RES720 has a single RF input for all the GNSS bands to simplify host circuitry. It uses dual SAW filters for exceptional signal selectivity and out-of-band attenuation thus providing the best total cost to performance ratio.

### Nanosecond-level Accuracy

The RES720 offers precision time synchronization with < 5 nanoseconds accuracy in normal mode of operation. RES720 is designed to meet stringent timing requirements of critical infrastructure and help operators maximize the performance of their networks and optimize the return on their infrastructure investments.

### Smart GNSS Assurance™

To protect against today's sophisticated attacks and signals meaconing, Protempis's timing module offers automatic detection and failover with highly reliable anti jamming and anti-spoofing capabilities.

### Advanced Security Features

With the ideals of zero trust security, the RES720 provides secure boot and antitampering features by default. Additionally, RES720 offers T-RAIM to provide the highest-level timing integrity.

### Protocols & Configuration

Protempis's timing modules support industry standard NMEA (National Marine Electronics Association) and TSIP (Protempis Standard Interface Protocol) for configuration and control.

### Embed in you design

Get your product to market faster by embedding the carrier board in your application. The carrier board is a proven design and fully tested.

Protempis is an industry leader in timing technology.



### Key Features

- ▶ Nanosecond-level timing accuracy (< 5 ns 1-sigma).
- ▶ Dual Band (L1 and L5) Multiconstellation GNSS timing module.
- ▶ Antenna OPEN/SHORT Detection
- ▶ RF Input Surge Protection
- ▶ Protection against jamming and spoofing with Protempis's Smart GNSS Assurance™.
- ▶ Advanced Security features that includes secure boot, secure interface and T-RAIM.
- ▶ Supports industry standard protocols such as NMEA and TSIP for configuration and Control.
- ▶ Advanced Multi-path Mitigation capabilities to distinguish and process directly received signal from reflected signals.

#### Disclaimer

Protempis does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others. Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or trade names, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.



## Interface Characteristics

- 2 Serial Ports
- RF input Connector: Right Angle SMB
- Digital I/O Connector  
single 16-pin (2x8) male header connector for both power and data I/O

## Dimension

Length: 2.6"  
Wide: 1.25"  
Mounting hole size: 0.125"

## Integrity Report

- T-RAIM active, phase uncertainty
- Time pulse rate/duty cycle, Interconstellation Biases

## Environmental Data, Quality & Reliability

- Operating temp. -40 °C to +85 °C
- Storage temp. -50 °C to +105 °C
- Humidity 5%-95% (non-condensing)
- RoHS compliant (lead-free)
- Green (halogen-free)
- ETSI-RED Complaint

## Electrical Data

- Supply voltage: 3.3VDC to ±5%
- Power consumption: 0.5W max

## Surge Protection

RF Input 6.0 V TVS diode with a peak pulse power dissipation of 600 W (10/1000 μs waveform)

## Timing Output

- 1 PPS (± 5ns)/PP2S
- Accuracy - < 5 ns (1-sigma, clear sky, absolute mode)

## Protocol

- NMEA
- TSIP

## Antenna Power Switch

+3.3 or +5V

## J3 Connector – PPS Output

U.FL (UMCC) Connector Receptacle, Male Pin

## J2 Connector – No Signal

U.FL (UMCC) Connector Receptacle, Male Pin

## Digital I/O Power connector Pinout

Pin	Function	Description
1	TXDB	Port B transmit, CMOS 3.3 V
2	Prime power input	+3.3 V DC ±0.3 V DC
3	TXDA	Port A transmit, CMOS 3.3 V
4	Sysclk (ICM 720 only)	No Signal
5	RXDA	Port A receive, CMOS 3.3 V
6	1PPS	One pulse-per-second, CMOS 3.3 V
7	RXDB	Port B receive, CMOS 3.3 V
8	GND	Ground, Power and Signal
9	Antenna power input	5 V DC, 55 mA max
10	Reset input	Reset
11	Reserved, do not connect	Reserved
12	Reserved, do not connect	Reserved
13	Reserved, do not connect	Reserved
14	Reserved, do not connect	Reserved
15	Reserved, do not connect	Reserved
16	Reserved, do not connect	Reserved

## Disclaimer

Prottempis does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others. Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or trade names, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.